

- L - Uncontrolled Lubrication
- BR - Return Line For Cylinders In Clamped Position
- AP - Pressure Line For Cylinders In Clamped Position
- BP - Pressure Line For Cylinders In Loading / Unloading Station
- AR - Return Line For Cylinders In Loading / Unloading Station



ROTARY DISTRIBUTION VALVE

Rotary Distribution Valves are available in various configuration . Multistation operations with various combinations ./ option for clamping / unclamping , uncontrolled lubrication etc .

OPERATING DATA :-

Max. Speed - ... RPM

Custom Built

MODEL	Ø `A`	Ø `B`	`C`	Ø `D`	`E`	`F`	`G`	`H` PORT	`I`	`J` PORT	`L`
RDV- * -02-00-G1/4"	40.91	70	M6	85	40	35	M8	1/4"	M6	1/4"	139.3
RDV- * -02-01-G1/4"	40.91	70	M6	85	40	35	M8	1/4"	M6	1/4"	174.3
RDV- * -02-00-G3/8"	58	100	1/8"	115	40	35	M8	3/8"	1/8"	3/8"	139.3
RDV- * -02-01-G3/8"	58	100	1/8"	115	40	35	M8	3/8"	1/8"	3/8"	174.3
RDV- * -02-00-G1/2"	67.52	122	1/4"	140	53	42	M8	1/2"	1/4"	1/2"	164.8
RDV- * -02-01-G1/2"	67.52	122	1/4"	140	53	42	M8	1/2"	1/4"	1/2"	206.8

* This area denotes No . of Working Station .
Please Specify in your order No . of Station Required

HOW TO ORDER

'FLUCONN' Product Code consists six sets of number .
Each set of number specify the feature , for Example
a Rotary Distribution Valve
ordering code RDV-06-02-01-01-G1/4" Would mean .

P - Product - Rotary Distribution Valve


S - No. of Stations

A - Single / Double acting


N - Loading / Checking Stations

C - No. of Uncontrolled Channels for Air / Lubrication


T - Threads in Ports




Product Code




No. of Stations
(2 - 16)




Cyl. Type
1- Single
2- Double



Loading Stations
(1 - 3)



Uncontrolled Lubrication Stations
(0 - 2)



Port Threads
(G 1/4" ,
G 3/8" ,
G 1/2")